



ENTRY GRATE



SECTION



HINGE DETAIL

NOTES

1. Entry grates are required on all pipes and R.C.B.C. entering an underground drainage system. Grates are not required on culverts under roadways.
2. All steel work shall be hot dipped galvanised to AS 1560 after fabrication.
3. All welds shall conform to AS 1554 and be 6mm C.F.W. unless noted otherwise.
4. Side bar protection to be provided only to headwalls with no wingwalls.
5. All dimensions are in millimetres.
6. All fittings and fixings to be S/S.

REVISIONS		DATE
C	MINOR TEXT AMENDMENT	23/10/17
B	MINOR AMENDMENTS	26/11/14
A	ORIGINAL ISSUE	12/03/04

**DISCLAIMER**

The authors and sponsoring organisations shall have no liability or responsibility to the user or any other person or entity with respect to any liability, loss or damage caused or alleged to be caused, directly or indirectly, by the adoption and use of these Standard Drawings including, but not limited to, any interruption of service, loss of business or anticipatory profits, or consequential damages resulting from the use of these Standard Drawings. Persons must not rely on these Standard Drawings as the equivalent of, or a substitute for, project-specific design and assessment by an appropriately qualified professional.



**STORMWATER DRAINAGE  
ENTRY GRATES**

Standard  
Drawing  
**S1100**

A	B	C	
---	---	---	--